



Product Type	Image	Category	Description	Price List
Senseface 2A - RFID PROXY		TIME ATTENDANCE & ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Identification Fingerprint Capacity : 3, 000 Face Capacity : 1500 RFID PROXY Card Capacity : 3000 Log Capacity : 150, 000 Communication : TCP/IP Standard Function : WIFI, ADMS , DST, Photo Capture, Event Photo Capture, Up to 14-digit User ID, Access Levels, Groups, Holidays, Record Query, Schedule Bell, Tamper Switch Alarm, Automatic Status Switch, Multiple AuthenticationMethods, SIP Client (Version 2.0), ONVIF (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q & Profile A), AC Push and TA Push Protocol Switch, HTTPs / SSH Backend Access, T9 Keyboard (Input)	3.794.000
Senseface 2A - MIFARE		TIME ATTENDANCE & ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Identification Fingerprint Capacity : 3, 000 Face Capacity : 1500 MIFARE Card Capacity : 3000 Log Capacity : 150, 000 Communication : TCP/IP Standard Function : WIFI, ADMS , Photo Capture, Event Photo Capture, Up to 14-digit User ID, Access Levels, Groups, Holidays, Record Query, Schedule Bell, Tamper Switch Alarm, Automatic Status Switch, Multiple AuthenticationMethods, SIP Client (Version 2.0), ONVIF (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q & Profile A), AC Push and TA Push Protocol Switch, HTTPs / SSH Backend Access, T9 Keyboard (Input)	4.393.000
MB20 - VL		TIME ATTENDANCE & ACCESS CONTROL	Face Capacity : 500 Finger Capacity : 500 ID Capacity :500 Log Capacity : 100.000 Standard Function : WIFI,ADMS , Automatic Status Switch, Self-Service Query, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID Lock, sensor, Exit button Colour : Black Language : Bahasa Indonesia / English Adaptor: Include inside box	2.446.000
SF300 - RFID PROXY		TIME ATTENDANCE & ACCESS CONTROL	Fingerprint Capacity : 1500 User/ RFID PROXY Card Capacity : 5000 Log Capacity : 80,000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report (adaptor Included) , Screen Size : 2,8 Inch Indonesia Language English / Bahasa	2.799.000
SF300 - MIFARE		TIME ATTENDANCE & ACCESS CONTROL	Fingerprint Capacity : 1500 User/ MIFARE Card Capacity : 5000 Log Capacity : 80,000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report (adaptor Included) , Screen Size : 2,8 Inch Indonesia Language English / Bahasa	3.409.000
MB460		TIME ATTENDANCE & ACCESS CONTROL	Face Capacity : 1500 Fingerprint Capacity : 2000 Card Capacity : 2000 Log Capacity : 100,000 Communication : TCP/IP, USB-host Standard Functions : ADMS, SMS, DST, Scheduled-bell, Self-service Query, Automatic Status Switch, T9 input, Photo ID, Camera, Multi-verification, RS232 Printer, 3rd party electric lock, Exit Button, Alarm.	3.557.000
MB40-VL (RFID PROXY)		TIME ATTENDANCE & ACCESS CONTROL	Fingerprint Capacity : 3000 Face Capacity : 3000 Card Capacity : 10,000 Standard Function : ADMS, Work Code, DST, Self Service-Query, Automark, Status Switch, T9 Input, Camera, 9 digit user ID, Multiple Verify Mode, Schedule Bell. Colour : Black Language : Bahasa Indonesia / English Adaptor : Include inside box	5.389.000
LX50		TIME ATTENDANCE - REPORT ONLY ON DEVICE	Fingerprint Capacity : 1000 User Capacity : 1000 Log Capacity : 50, 000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report	Rp 945.000
LX14		TIME ATTENDANCE - REPORT ONLY ON DEVICE	Fingerprint Capacity : 1000 User Capacity : 1000 Log Capacity : 50, 000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report	Rp 945.000
IN02 (ID)		TIME ATTENDANCE & ACCESS CONTROL	Fingerprint Capacity: 3000 ID Card Capacity:10, 000 Log Capacity: 100, 000 Communication: TCP/IP, USB(host&Client), RS232/485 Standard Functions: Work Code, DST, Short Message, Self Service Query, 5 Digit User ID, Multiple Verify Mode, T9 Input, Automatic Status Switch, Backup Battery, Wiegand In&Out, Anti-passback, ADMS Language : English / Bahasa Indonesia	5.119.000
MINI AC (WIFI)		ACCESS & TIME ATTENDANCE	ID Capacity : 1000 Face Capacity : 800 Palm Capacity : 800 Log Capacity : 150.000 Standard Function : WIFI , ID Card, ADMS , T9 Input, DST, Camera, 9 digit user ID, Access Levels, Groups, Holidays, Anti-passback, Record Query, Tamper Switch Alarm, Multiple Verify Modes, TCP/IP, Wiegand input/output, RS485 Colour : Black	4.580.000

MINI AC PLUS (WIFI)		ACCESS & TIME ATTENDANCE	ID Capacity : 3000 Face Capacity : 3000 Palm Capacity : 1500 Log Capacity : 150,000 Standard Function : ID Card, ADMS, T9 Input, DST, Camera, 9 digit user ID, Access Levels, Groups, Holidays, Anti-passback, Record Query, Tamper Switch Alarm, Multiple Verify Modes, TCP/IP, Wiegand input/output, RS485 Colour : Black Language : Bahasa Indonesia / English Adaptor: Include inside box"	5.460.000
MINI AC PLUS MIFARE		ACCESS & TIME ATTENDANCE	MIFARE CARD Capacity : 3000 Face Capacity : 3000 Palm Capacity : 1500 Log Capacity : 150,000 Standard Function : Mifare Card, ADMS, T9 Input, DST, Camera, 9 digit user ID, Access Levels, Groups, Holidays, Anti-passback, Record Query, Tamper Switch Alarm, Multiple Verify Modes, TCP/IP, Wiegand input/output, RS485 Colour : Black Language : Bahasa Indonesia / English Adaptor: Include inside box"	5.770.000
UA500		TIME ATTENDANCE	Fingerprint Capacity : 3000 Log Capacity : 100, 000 Communication : TCP/IP, RS232/485, USB(host & client) Standard Functions : Webserver, Work Code, DST, Self Service Query, 9 Digit User ID, T9 Input, Schedule-bell, Automatic Status Switch, Language : Bahasa Indonesia / English	3.415.000
K20 Pro (RFID + BATTERY)		TIME ATTENDANCE	Fingerprint Capacity: 3,000 ID Card Capacity: 1,000 Log Capacity: 100, 000 Communication: TCP/IP, USB Host Standard Functions: Work Code, Short Message, DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report, Multiple Verify Mode, Simple Access Control, Backup Battery Language : Bahasa Indonesia / English	1.915.000
F18 - RFID		ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Identification Fingerprint Capacity : 3, 000 ID Card Capacity : 5000 Log Capacity : 100, 000 Communication : TCP/IP, RS232/485, Anti-passback, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Adaptor Included Wiegand input&output	3.700.000
F18 - MIFARE		ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Identification Fingerprint Capacity : 3, 000 ID Card Capacity : 5000 Log Capacity : 100, 000 Communication : TCP/IP, RS232/485, Anti-passback, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Adaptor Included Wiegand input&output	4.310.000
F19 - RFID		ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Capacity : 3, 000 Card Capacity : 5,000 (optional) Log Capacity : 30, 000 Communication : TCP/IP, RS232/485, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Wiegand input&output Language : Bahasa Indonesia / English	3.700.000
F19 - MIFARE		ACCESS CONTROL	2.4 inch TFT-LCD screen Fingerprint Capacity : 3, 000 Card Capacity : 5,000 (optional) Log Capacity : 30, 000 Communication : TCP/IP, RS232/485, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Wiegand input&output Language : Bahasa Indonesia / English	4.310.000
SC105 - RFID		ACCESS CONTROL	Card Capacity: 30, 000 Log Capacity: 80, 000 Communication: TCP/IP, RS232/485, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Wiegand input&output 1 ea Aux. input for linkage function	2.719.000
SC105 - MIFARE		ACCESS CONTROL	Card Capacity: 30, 000 Log Capacity: 80, 000 Communication: TCP/IP, RS232/485, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button and door bell. Wiegand input&output 1 ea Aux. input for linkage function	2.990.000
X8S		ACCESS CONTROL	Fingerprint/Card/Password Identification Fingerprint Capacity : 500 Card Capacity : 500 ZK Optical Sensor, ZKFinger VX10.0 Communication : N/A Access Control Interface for electric lock, door sensor, alarm, exit button and door bell.	1.078.000
MA300		ACCESS CONTROL	Fingerprint and RFID Identification Metal Casing, IP65 waterproof and dustproof Fingerprint Capacity: 1, 500 ID card Capacity: 10, 000 Log Capacity: 100, 000 Communication: TCP/IP, RS485, USB Host Access Control Interface for electric lock, door sensor, alarm, exit button.	3.665.000

ProRF - RFID		ACCESS CONTROL	RFID Identification ID card Capacity: 60, 000 Log Capacity: 600, 000 Communication: TCP/IP, RS232/485, Wiegand Input/Output Access Control Interface Lock Relay Output, Aux Input, exit button, Doorbell output	2.559.000
ProRF - MIFARE		ACCESS CONTROL	MIFARE Identification ID card Capacity: 60, 000 Log Capacity: 600, 000 Communication: TCP/IP, RS232/485, Wiegand Input/Output Access Control Interface Lock Relay Output, Aux Input, exit button, Doorbell output	3.168.000
LF10 -RFID		Time Attendance / Access control	Display: 2.4 inch TFT LCD Color Screen (keypad) Fingerprint Capacity:1,500 Templates RFID PROXY card capacity : Log Capacity: 80, 000 Transactions Communication: TCP/IP, USB-host Access Control Interface: 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell, Wiegand Out Aux. Input:1ea for linkage function Standard Function: Record Query, 9-digit User ID, ADMS , ID Card, Advanced access control, Wired doorbell AC Adapter: 12V DC, 1.5A	2.695.000
LF10 - Mifare		Time Attendance / Access control	Display: 2.4 inch TFT LCD Color Screen (keypad) Fingerprint Capacity:1,500 Templates MIFARE card capacity : Log Capacity: 80, 000 Transactions Communication: TCP/IP, USB-host Access Control Interface: 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell, Wiegand Out Aux. Input:1ea for linkage function Standard Function: Record Query, 9-digit User ID, ADMS , ID Card, Advanced access control, Wired doorbell	2.963.000
LF20 -RFID (KIT)		Time Attendance / Access control	Display: 2.4 inch TFT LCD Color Screen (keypad) Fingerprint Capacity:1,500 Templates Transaction Capacity: 80, 000 Transactions Algorithm Version: ZKFinger VX10.0 Communication: TCP/IP, USB-host Access Control Interface: 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell, Wiegand Out Aux. Input:1ea for linkage function Standard Function: Record Query, 9-digit User ID, ADMS , ID Card, Advanced access control, Wired doorbell AC Adapter: 12V DC, 1.5A Operating Temperature: 0 °C- 45 °C Operating Humidity: 20%-80% SDK: Push SDK Package with Electric Bolt Lock: 1* LF10 Access Control Terminal with Installation Guide & Quick Start Guide and cables; 1* TLEB102 Non touch Exit Button with Installation Guide; 1* LM-2805 Electronic Magnetic Lock with User manual and 1*LMB-280U Lock Bracket;	3.772.000
LF20 - Mifare (KIT)		Time Attendance / Access control		4.041.000
GL300 - 1 remote		ACCESS GLASS DOOR LOCK	User capacity: 100 Fingerprint Capacity: 300 MF Card Capacity: 300 Password Capacity: 300 Remote key function Door bell function OLED Display Door Thickness:10-12 mm Color Option: Black	4.145.000
I Clock 9000 (Batt)		ACCESS CONTROL	Fingerprint Identification Fingerprint Capacity : 3, 000 Card Capacity : 3,000 Log Capacity : 200.000 Communication : TCP/IP, USB-Host, GPRS, SMS, DTS, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 Input,Multi-verification, 12V Output, RS232 Printer (Optional Cable), Work code,ADMS, 9 Digit User ID, ID Card	5.274.000
SF400		ACCESS CONTROL	Screen Size : 2,8 Inch Fingerprint Capacity : 1500 Log Capacity : 80,000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report (adaptor Included) Language English / Bahasa Indonesia	2.544.000
SF200		ACCESS CONTROL	Screen Size : 2,8 Inch Fingerprint Capacity : 1500 User/Card Capacity : 5000 Log Capacity : 80,000 Communication : USB Host and Client Standard Functions : DST, Self Service Query, 9 Digit User ID, Automatic Status Switch, Schedule-bell, T9 Input, SSR Report (adaptor Included) Language English / Bahasa Indonesia	2.886.000
C3-100 PACKAGE		CONTROLLER PANEL	One-door Two-way Controller CPU:32bit MIPS CPU RAM:32M bits Flash Memory:256M bits User:30, 000 Event Buffer: 100, 000 Reader Port: 2ea (26/34bits wiegand, 8bits burst for PIN) Communication: RS485, TCP/IP A package of C3-100 including Metal box and PSU(Power Supply Unit)	3.851.000
C3-200 PACKAGE		CONTROLLER PANEL	Two-door Two-way Controller CPU:32bit MIPS CPU RAM:32M bits Flash Memory:256M bits User:30, 000 Event Buffer: 100, 000 Reader Port:2ea (26/34bits wiegand, 8bits burst for PIN) Communication: RS485, TCP/IP A package of C3-200 including Metal box and PSU(Power Supply Unit)	5.057.000

C3-400 PACKAGE		CONTROLLER PANEL	Four-door One-way Controller CPU:32bit MIPS CPU RAM:32M bits Flash Memory:256M bits User:30, 000 Event Buffer:100, 000 Reader Port:4ea(26/34bits wiegand, 8bits burst for PIN) Communication: RS485, TCP/IP A package of C3-400 including Metal box and PSU(Power Supply Unit)	6.397.000
InBio 160		CONTROLLER PANEL	Number of doors controller 1 Door Numbers of readers supported 4(2 RS-485 Reader, 2 (26-bit wiegand reader) Types of readers supported 26-bit Wiegand and RS485 FR Series Reader Number of Inputs 3 (1 exit Device and Door Status, 1 AUX) Number of Outputs 2 (1-Form C Relay for Lock and One Form C Relay for Aux Output) Card holders Capacity 30,000 Fingerprint Capacity 3,000 Log Events Capacity 100,000 Communication TCP/IP and RS-485	4.265.000
InBio 260		CONTROLLER PANEL	Number of doors controller 2 Door Numbers of readers supported 8(4 RS-485 Reader, 4(26-bit wiegand reader) Types of readers supported 26-bit Wiegand and RS485 FR Series Reader Number of Inputs 3 (2exit Device and Door Status, 1 AUX) Number of Outputs 4 (2-Form C Relay for Lock and 2 Form C Relay for Aux Output) Card holders Capacity 30,000 Fingerprint Capacity 3,000 Log Events Capacity 100,000 Communication TCP/IP and RS-485	8.579.000
InBio 460		CONTROLLER PANEL	Number of doors controller 4 Door Numbers of readers supported 12(8 RS-485 Reader, 4 26-bit wiegand reader) Types of readers supported 26-bit Wiegand and RS485 FR Series Reader Number of Inputs 3 (exit Device and Door Status, 1 AUX) Number of Outputs 8 (4-Form C Relay for Lock and 4 Form C Relay for Aux Output) Card holders Capacity 30,000 Fingerprint Capacity 3,000 Log Events Capacity 100,000 Communication TCP/IP and RS-485	11.642.000
KR500E		CARD READER	Read 125KHz Proximity ID card number Wiegand output 26bit Dimension: 44*78*16mm	324.000
KR500M		CARD READER	Read 13.56MHz Mifare card number Wiegand output 34bit Dimension: 44*78*16mm	434.000
LM2805		EM-LOCK 600LBS	Suitable for door : inswing door degree door aluminium Suit for 280Kg Opening mode : 90 Finished for shell :Anoddixed Magnetic lock Size 250x50x30mm	676.000
LMB280ZL		BRACKET EM-LOCK	Suitable for door : inswing door degree door aluminium Suit for 280Kg Opening mode : 90 Finished for shell :Anoddixed Magnetic lock Size 250x50x30mm	297.000
LB-12		DROP BOLT	Size 204Lx35Wx39H mm Aluminum body case Full metal Mechanical Structure Bolt : SUS304 solid stainless steel bolt Voltage : DC12V-DC24V Active Current : 120mA Induction current 12mA Induction Distance 8 mm Force Holding 1000 Kg	703.000
LBB		DROP BOLT BRACKET	Size 93LX49Wx38H mm Glass Thickness : 10 -15 cm suitable Fully frameless Glass Door Opening Mode 180 Degree Door Finised for Shell : Stainless Steel Wire Drawing	163.000
TLEB1		CONTACTLESS EXIT BUTTON	115*70*39mm, Touchless Sensor; No Touch; ANSI Size; Standby : Blue Light, Active: Green Light	249.000
TLEB2		CONTACTLESS EXIT BUTTON	Touchless Sensor; No Touch; ANSI Size; Standby : Blue Light, Active: Green Light	249.000
EB1		EXIT BUTTON	70*14*20mm; Ultra Narrow Small; Surface Mount;	39.000
LH3000		HOTEL LOCK	Stainless steel Casing With advanced 13.56mhz MIFARE-1 card technology With free hotel lock management software Door Thickness: 35-55 mm Backset: 62.5 mm Color Option:silver	1.886.000
LH6500		HOTEL LOCK	Zinc Alloy Casing With advanced 13.56mhz MIFARE-1 card technology With free hotel lock management software Door Thickness: 40-50 mm Backset: 62.5 mm Color Option: Black	2.589.000
LH7500		HOTEL LOCK	Zinc Alloy Casing With advanced 13.56mhz MIFARE-1 card technology With free hotel lock management software Door Thickness: 35-55 mm Backset: 62.5 mm Color Option: Black	3.772.000

L5000		SMART LOCK	Zinc Alloy Metal Casing Fingerprint Capacity: 500 Password Capacity: 100 Card Capacity: 100 Log Capacity: 30,000 Communication: USB-Host Door Thickness: 35-55 mm Backset: 55 mm ID Card Color Option: Polished Chrome	5.243.000
AL20B		SMART LOCK	Zinc Alloy American Mortise Door Thickness 30-54mm (standard) User Capacity : 100 Password Capacity : 100 Fingerprint Capacity : 100	3.797.000
TL400B		SMART LOCK	Zinc Alloy Metal Casing Fingerprint Capacity: 100 ID Card Capacity: 100 Password Capacity: 100 Communication: USB-Host/Bluetooth Door Thickness: 35-54 mm Backset: 55mm Color Option: silver+Black mask App: ZK Smartkey	4.922.000